

United States Patent and Trademark Office

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO. FILING DATE		FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.	
10/723,389	10/723,389 11/25/2003		Thomas Redden Veariel	2003B103/2	8869
23455	7590	08/17/2006	EXAM	EXAMINER	
212120111	IOBIL CH	EMICAL COMPA	DEL SOLE, JOSEPH S		
P.O. BOX :		, E	ART UNIT	PAPER NUMBER	
BAYTOW	N, TX 775	522-2149	1722		

DATE MAILED: 08/17/2006

Please find below and/or attached an Office communication concerning this application or proceeding.

		Application No.		Applicant(s)						
Office Action Summary			10/723,389		VEARIEL ET AL.					
			Examiner		Art Unit					
			Joseph S. De	Sole	1722					
	The MAILING DATE of this communication appears on the cover sheet with the correspondence address Period for Reply									
A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION. - Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication. - If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication. - Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).										
Status										
1)[[]	Responsive to communication(s) file	d on <i>08 Ju</i>	ne 2006							
•	This action is FINAL . 2b)⊠ This action is non-final.									
,—		<i>'</i> —			secution as to the	e merits is				
· ·	Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under <i>Ex parte Quayle</i> , 1935 C.D. 11, 453 O.G. 213.									
Dispositio	on of Claims				•					
		nnlication								
-	Claim(s) 1-72 is/are pending in the application.									
	4a) Of the above claim(s) <u>1-35 and 66-71</u> is/are withdrawn from consideration.									
-	Claim(s) is/are allowed.									
•	Claim(s) <u>36-65 and 72</u> is/are rejected.									
·	Claim(s) is/are objected to.	ion andlar	alastian magu	iramant						
، اــا(ه	Claim(s) are subject to restrict	lion and/or	election requ	rement.						
Application	on Papers									
9)□ T	The specification is objected to by the	Examiner	•.							
10)□ T	The drawing(s) filed on is/are:	a) acce	epted or b)	objected to by the E	xaminer.					
,	Applicant may not request that any objec	tion to the d	Irawing(s) be h	eld in abeyance. See	37 CFR 1.85(a).					
1	Replacement drawing sheet(s) including	the correction	on is required i	the drawing(s) is obj	ected to. See 37 Cl	FR 1.121(d).				
11) The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.										
Priority u	nder 35 U.S.C. § 119		•							
 12) Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f). a) All b) Some * c) None of: 1. Certified copies of the priority documents have been received. 2. Certified copies of the priority documents have been received in Application No. 3. Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)). * See the attached detailed Office action for a list of the certified copies not received. 										
2) 🔲 Notice 3) 🔯 Inform	of References Cited (PTO-892) of Draftsperson's Patent Drawing Review (PT ation Disclosure Statement(s) (PTO-1449 or FNo(s)/Mail Date 11/2003.		4) 5) 6)	Interview Summary (Paper No(s)/Mail Da Notice of Informal Pa Other:	te	O-152)				

Application/Control Number: 10/723,389 Page 2

Art Unit: 1722

DETAILED ACTION

Election/Restrictions

- 1. Claims 1-35 and 66-71 are withdrawn from further consideration pursuant to 37 CFR 1.142(b), as being drawn to a nonelected invention, there being no allowable generic or linking claim. Applicant timely traversed the restriction (election) requirement in the reply filed on 6/8/06.
- 2. Applicant's election with traverse of claims 36-64 and 72 in the reply filed on 6/8/06 is acknowledged. The traversal is on the ground(s) that a search on all inventions would not be unduly burdensome. This is not found persuasive because the non-elected inventions require searches in classes and subclasses not required for the search for the claimed invention.

The requirement is still deemed proper and is therefore made FINAL.

Trademark Objections

3. The use of the trademark Inconel has been noted in this application. It should be capitalized wherever it appears and be accompanied by the generic terminology. In the claims, the generic term <u>must</u> be used solely.

Although the use of trademarks is permissible in patent applications, the proprietary nature of the marks should be respected and every effort made to prevent their use in any manner which might adversely affect their validity as trademarks.

Claim Rejections - 35 USC § 112 *

4. The following is a quotation of the second paragraph of 35 U.S.C. 112:

The specification shall conclude with one or more claims particularly pointing out and distinctly claiming the subject matter which the applicant regards as his invention.

Application/Control Number: 10/723,389 Page 3

Art Unit: 1722

5. Claim 72 is rejected under 35 U.S.C. 112, second paragraph, as being indefinite for failing to particularly point out and distinctly claim the subject matter which applicant regards as the invention.

Claim 72 is vague and indefinite because it is unclear whether it is a product claim (it is dependent on product claim 27) or an apparatus claim (its preamble and all its limitations are apparatus only). The claim will be treated as an apparatus claim only and its dependence must be amended for consistency.

Claim Objections

- 6. Claim 72 is objected to under 37 CFR 1.75(c), as being of improper dependent form for failing to further limit the subject matter of a previous claim. Applicant is required to cancel the claim(s), or amend the claim(s) to place the claim(s) in proper dependent form, or rewrite the claim(s) in independent form. Claim 72 fails to include any product limitations and thus fails to further limit parent claim 27. As stated above, claim 72 will be treated as an apparatus claim.
- 7. Claim 65 is objected to under 37 CFR 1.75(c), as being of improper dependent form for failing to further limit the subject matter of a previous claim. Applicant is required to cancel the claim(s), or amend the claim(s) to place the claim(s) in proper dependent form, or rewrite the claim(s) in independent form. The limitation "retrofit part" does not structurally differentiate the apparatus from merely being a second plate, since "retrofit part" speaks to the method by which the second plate came into existence and not its structural qualities.

Application/Control Number: 10/723,389

Art Unit: 1722

Claim Rejections - 35 USC § 102

8. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless -

- (b) the invention was patented or described in a printed publication in this or a foreign country or in public use or on sale in this country, more than one year prior to the date of application for patent in the United States.
- 9. Claims 36-38, 44, 47, 51-53, 56, 58-59, 62 and 65 are rejected under 35 U.S.C. 102(b) as being anticipate by Courval et al (5,204,045).

Courval et al teach a die plate having (Fig 3, #25) (a) an upstream face; (b) a downstream face; (c) at least one passage having a first opening in said upstream face whereby molten resin may be received and a second opening in said downstream face whereby molten resin may be extruded; and (d) a heater (Fig 3, #28) proximate said downstream face and proximate with said at least one passage at said downstream opening; the at least one passage is generally cylindrical and having a substantially uniform diameter from said upstream face to said downstream face (Fig 3); the heater is concentric with said at least one passage (Fig 3); the die plate is a monolithic die plate (Fig 3); die plate comprises a first plate having said upstream face and a second plate having said downstream face and said heater, said first and second plates fluidically connected by said at least one passage (the broadness of the claims shows that Courval et al reads on this, with #14 being the first plate and #25 being the second plate); the at least one passage passes through a portion of said heater, such that said portion defines the wall of said passage proximate said downstream face (an alternative embodiment of Courval et al reads on this, col 8, lines 9-11); the die plate comprises a

Page 5

Art Unit: 1722

material selected from brass, stainless steel, and Inconel.TM (col 2, lines 40-55); an extrusion die assembly having a die plate having at least one passage including an initial, upstream zone comprised of an opening for receiving a polymer melt having a bulk temperature, an intermediate zone for conveying said polymer melt, and a final, downstream zone terminating said extrusion die assembly at an exit opening whereby said polymer melt exits said extrusion die assembly, further comprising a heating means for said downstream zone whereby at least a portion of said polymer melt may be locally heated to a temperature greater than T (Fig 3); the heating means comprises a heater concentric with the extrusion orifice pattern (Fig 3); the heating means is proximate said exit opening; the passage is generally cylindrical and having a substantially uniform diameter from said opening for receiving a polymer melt to said exit opening (Fig 3); the die plate is a monolithic die plate (Fig 1) the die plate comprises a first plate having an upstream face and comprising said upstream zone and a second plate having a downstream face and said heater, said first and second plates fluidically connected by said at least one passage (see discussion above); the die plate comprises a material selected from brass, stainless steel, and Inconel.TM (col 2. lines 40-55); the second plate is a retrofit part (Fig 3).

10. Claims 36, 38, 40, 42,47, 51, 52, 53, 54, 55 are rejected under 35 U.S.C. 102(b) as being anticipated by Bentivoglio et al (4,830,595).

Bentivoglio et al teach a die plate (Fig 1, #s 60 and 80) having (a) an upstream face; (b) a downstream face; (c) at least one passage having a first opening in said upstream face whereby molten resin may be received and a second opening in said

Art Unit: 1722

downstream face whereby molten resin may be extruded; and (d) a heater (Fig 2, #s 64 and 84) proximate said downstream face and proximate with said at least one passage at said downstream opening; the heater is concentric with said at least one passage (Fig 2); an insulation material (Fig 2, spaces 86, 87, 66 and 67) contiguous with said heater and the die plate and concentric with said heater about said at least one passage proximate said downstream opening (Fig 2); an insulation material (Fig 2, spaces 66, 67, 86, and 87) concentric with said at least one passage and contiguous with at least a portion of said heating means, and contiguous with said at least one passage at said exit opening; the die plate is a material selected from brass, stainless steel, and Inconel.TM (col 5, lines 5-20, the Examiner notes that although in some parts aluminum may be preferred, steel is taught for all claimed parts of the die); an extrusion die assembly comprising a die plate having at least one passage including an initial, upstream zone comprised of an opening for receiving a polymer melt having a bulk temperature T.sub.melt, an intermediate zone for conveying said polymer melt, and a final, downstream zone terminating said extrusion die assembly at an exit opening whereby said polymer melt exits said extrusion die assembly, further comprising a heating means for said downstream zone whereby at least a portion of said polymer melt may be locally heated to a temperature greater than T.sub.melt (Fig 2); the heating means comprises a heater concentric with the extrusion orifice pattern (Fig 1); the heating means is proximate said exit opening; the downstream zone further comprising an insulation material concentric with said passage and contiguous with at least a portion of said heating means and said die assembly (Fig 2); the downstream zone

Application/Control Number: 10/723,389

Art Unit: 1722

further comprises an insulation material concentric with said passage and contiguous with at least a portion of said heating means, and contiguous with said passage at said exit opening (Fig 2); the die plate comprises a material selected from brass, stainless steel, and Inconel.TM (see above).

11. Claims 36, 38-42, 44-55, 57, 59-65 and 72 rejected under 35 U.S.C. 102(b) as being anticipated by Dudley (4,123,207).

Dudley teaches a die plate having (Fig 4) having: (a) an upstream face; (b) a downstream face; (c) at least one passage having a first opening in said upstream face whereby molten resin may be received and a second opening in said downstream face whereby molten resin may be extruded; and (d) a heater (Fig 4, #s 410, 440, et al) proximate said downstream face and proximate with said at least one passage at said downstream opening; the heater is concentric with said at least one passage (Fig 4); the at least one passage passes through a portion of said heater, such that said portion defines the wall of said passage proximate said downstream face (Fig 4); having an insulation material (Fig 4, #s 815A and B) contiguous with said heater and said die plate and concentric with said heater about said at least one passage proximate said downstream opening; having an insulation material (Fig 4, #s 430 and 431) concentric with said at least one passage proximate said downstream face and forming at least a portion of said downstream face at said second opening; having an insulation material concentric with said at least one passage and contiguous with at least a portion of said heating means, and contiguous with said at least one passage at said exit opening (Fig. 4); the die plate comprises a first plate having said upstream face and a second plate

Art Unit: 1722

having said downstream face and said heater, said first and second plates fluidically connected by said at least one passage (Fig 4); having a plurality of said at least one passage and wherein said first and second plates are fluidically connected by each of said at least one passage (Fig 4); having a plurality of said at least one passage; the die plate comprises a material selected from brass, stainless steel, and Inconel.TM (col 3, line 60 - col 4, line 2 and col 5, lines 30-50); the insulation material is selected from high temperature plastics, machineable ceramics, ceramics which may be deposited by spray coating techniques, and ceramics which may be deposited by vapor deposition techniques (col 4, lines 20-30); an extrusion die assembly comprising a die plate having at least one passage including an initial, upstream zone comprised of an opening for receiving a polymer melt having a bulk temperature T.sub.melt, an intermediate zone for conveying said polymer melt, and a final, downstream zone terminating said extrusion die assembly at an exit opening whereby said polymer melt exits said extrusion die assembly, further comprising a heating means for said downstream zone whereby at least a portion of said polymer melt may be locally heated to a temperature greater than T.sub.melt (Fig 4); having a heater concentric with the extrusion orifice pattern (Fig 4); the heating means is proximate said exit opening (Fig 4); the downstream zone further comprising an insulation material concentric with said passage and contiguous with at least a portion of said heating means and said die assembly (Fig 4); the downstream zone further comprises an insulation material concentric with said passage and contiguous with at least a portion of said heating means, and contiguous with said passage at said exit opening (Fig 4); the die plate comprises a plurality of said at least

Art Unit: 1722

one passage (Fig 4); the die plate comprises a first plate having an upstream face and comprising said upstream zone and a second plate having a downstream face and said heater, said first and second plates fluidically connected by said at least one passage; the die plate has a plurality of said at least one passage (Fig 4); a plurality of the at least one passage and wherein said first and second plates are fluidically connected by each of said at least one passage (Fig 4); the die plate has a material selected from brass, stainless steel, and Inconel.TM (see above); the insulation material is selected from high temperature plastics, machineable ceramics, ceramics which may be deposited by spray coating techniques, and ceramics which may be deposited by vapor deposition techniques; the second plate is a retrofit part (Fig 4).

References of Interest

12. Lengerich et al (6,595,765), Lambertus (4,934,916), Bertolotti (4,678,423), Knight et al (6,976,834), Yoshii et al (6,638,045); Wolfe, Jr (4,378,964), Gove et al (3,427,685), Swickard et al (3,461,496), Ready (6,474,969), Matsuo (5,714,173), Mizuno et al (4,178,067), Ishida (6,514,062), Lambertus (4,764,100), Wolfe, Jr (4,752,196), Remscheid (3,749,536), Okita (4,225,547) and Braun (3,516,120) are cited of interest to show the state of the art.

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Joseph S. Del Sole whose telephone number is (571) 272-1130. The examiner can normally be reached on M-F 8:30 - 5.

Application/Control Number: 10/723,389 Page 10

Art Unit: 1722

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Yogendra Gupta can be reached on (571) 272-1316. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

Joseph S. Del Sole

JOSEPH S. DEL SOLE PRIMARY EXAMINER

8/15/06